

PIPE BOLLARD DIMENSIONS			FOOTING DIMENSIONS	
NOMINAL PIPE SIZE	OUTSIDE DIAMETER	ANCHOR BAR SIZE	MINIMUM DIAMETER	MINIMUM DEPTH
3"	3.50"	¾"ø X 6"	12"	2'-6"
4"	4.50"	¾"ø X 8"	14"	3'-0"
6"	6.625"	¾"ø X 12"	20"	3'-0"

SEE NOTES ON SHEET 2



FIXED STEEL BOLLARD

REVIEWED BY THE PARK STANDARDS COMMITTEE, AND APPROVED BY THE CHIEF OF DESIGN & CONSTRUCTION

L Ganza

10/01/2020

102 SHEET 1 OF 2

NOT TO SCALE

STD PLAN

EAST BAY REGIONAL PARK DISTRICT - STANDARD PLANS

FABRICATION

- PIPE TO BE STANDARD WEIGHT (SCH 40) ASTM A135 GALVANIZED STEEL.
- 2. PIPE CAP TO BE STANDARD WEIGHT, BUTT WELD TYPE, WITH BEVELED EDGE.
- 3. WELDERS TO BE AWS CERTIFIED AND PREQUALIFIED FOR THE WELDING TO BE PERFORMED.
- 4. THOROUGHLY CLEAN AND PROFILE THE SURFACES TO BE PAINTED. FOLLOW RECOMMENDATIONS IN THE "GUIDE TO PREPARING HOT—DIP GALVANIZED STEEL FOR PAINT" PUBLISHED BY THE AMERICAN GALVANIZERS ASSOCIATION (AGA) HTTPS: //GALVANIZEIT.ORG.
- 5. PRIME AND PAINT TOP 42" (MINIMUM) OF BOLLARD "EBRPD BROWN METAL" PER STD PLAN 003 PAINT SPECIFICATION.

INSTALLATION

- 6. LOCATE UNDERGROUND UTILITIES PRIOR TO DIGGING. CALL USA (UNDERGROUND SERVICE ALERT) 1-800-277-2600, MON THRU FRI 6AM TO 7PM, A MINIMUM 2 WORKING DAYS WITH A MAXIMUM 14 CALENDAR DAYS, TO OBTAIN A TICKET. CONTACT THE DISTRICT INSPECTOR OR PARK SUPERVISOR FOR DISTRICT UTILITIES NOT LOCATED BY USA.
- 7. CONCRETE TO BE COMMERCIAL 5-SACK PRE-MIX CONCRETE OR EQUIVALENT.
- 8. TOUCH-UP ANY DAMAGED FINISH AFTER INSTALLATION.
- 9. REFLECTIVE SAFETY TAPE TO BE 3" WIDE YELLOW, RATED FOR 5 YEAR MIN OUTDOOR LIFE AND MEET D.O.T. SPECIFICATION FP-85 FOR TYPE 2 SHEETING.
- 10. EBRPD BOLLARD DETAIL MAY NOT MEET THE PROTECTION REQUIREMENTS OF PG&E AND OTHER AGENCIES. WHERE APPLICABLE, USE STANDARD PLANS PROVIDED BY AGENCY HAVING JURISDICTION.



FIXED STEEL BOLLARD - NOTES

REVIEWED BY THE PARK STANDARDS COMMITTEE, AND APPROVED BY THE CHIEF OF DESIGN & CONSTRUCTION

L Ganza

10/01/2020

102 SHEET 1 OF 2

STD PLAN

NOT TO SCALE